

MARK SAFETY APPLIANCES

Regd. Office and Warehouse:

Plot No. 92, 93, Shah Industrial Park-3 at Kotambi, Pin Code 391510, Vadodara-Halol Highway, Dist. Vadodara, Gujarat, India.

■ 02668 299065, 098797 79661 info@marksafety.com

GST No: 24AABPZ7907Q1ZW

MSME No: UDYAM-GJ-24-0020651

MOBILE FOAM TROLLEY UNIT

FRP BODY, 150 LTRS CAPACITY

Mobile foam trolley units are mobile foam compound tanks fitted with foam branches and inductors, and having arrangement to carry hoses. Ideal for quick mobilization of foam equipment and application of foam, especially for areas such as Oil depots, Paint/ Solvent storage areas, Petrochemical complexes, etc.

Brief Description: AAAG Mobile Foam Trolley Unit MFT150-F, consisting of FRP tank (150 Ltrs capacity), suitably mounted on sturdy chassis/frame for easy maneuverability. Arrangements provided to mount low/medium expansion Foam Branch and matching Inline Inductor of 225/450 lpm capacity, as well as two nos. 15 Mtrs long Fire fighting Delivery hoses.

1.0	GENEKAL	DATA

1.1	Make	AAAG
1.2	Model	MFT150-F
1.3	Capacity	150 Ltrs

1.4 Foam Equipment Foam Branch (225/450 lpm) with matching Inline Inductor

1.5 Reference

2.0 MATERIAL OF CONSTRUCTION

2.	1 Tank	FRP
∠.		1 131

2.2 Chassis frame		M.S. / SS 304	
2.3	Wheels	Solid polymer	
2.4	Hara kaskas	CC 204	

2.4 Hose basket SS 304

2.5 Alu. IS 7882-1975/ SS304 Foam Branch 2.6 Inline Inductor Alu. IS 7882-1975/ SS304

3.0 **TESTING AND QUALITY CONTROL**

3.1 Performance Requirements Easy maneuverability of Trolley unit. Flow test as per

branch/inductor capacity.

Documentation Internal inspection report, supplier's certificates, approved 3.2

laboratory test certificates

OPERATIONAL/ TECHNICAL DATA 4.0

4.1 Working pressure (for Foam Eqpt) 7 to 10 Kgf/cm2

FB 5 (225 lpm at 7 kg/cm2) & matching Inline Inductor or 4.2 Branch/Inline Inductor

FB 10 (450 lpm at 7 kg/cm2) & matching Inline Inductor.

4.3 Hoses RRL or Synthetic Hoses, 15 Mtrs length (2 Nos).

5.0 **FINISH**

5.1 Painted Bright yellow colour Tank

5.2 Branch/Inline Inductor Painted Fire Red Color IS: 5 Shade No 536

5.3 SS parts Natural shining finish

APPROVALS & MARKING 6.0

6.1 **Approvals**

6.2 Marking AAAG/ Year of Mfg./ Capacity/ SL. No

7.0 WARRANTY

12 Months from the date of supply 7.1 Warranty & Guarantee




MARK SAFETY APPLIANCES

Regd. Office and Warehouse: Plot No. 92, 93, Shah Industrial Park-3 at Kotambi, Pin Code 391510, Vadodara-Halol Highway, Dist. Vadodara, Gujarat, India.

GST No: 24AABPZ7907Q1ZW **MSME No:** UDYAM-GJ-24-0020651

02668 299065, 098797 79661 info@marksafety.com





1	Tank	FRP
2	Foam Branch Pipe	Alu. IS:7882-1975
3	Inline Inductor	Alu. IS:7882-1975
NO.	DESCRIPTION	MATERIAL
PART LIST		

Mobile Foam Unit, 150 Ltrs Capacity, FRP Body, Conventional Design			
SCALE	DRAWING NO:	SHEET	REV.
N.T.S	F270-150BJ	1 OF 1	0